PRESSIZA 101 PERFORMANCE GUIDE

pressiza

Features

- White, highgloss sheet specially engineered for use in ondemand ink jet printers
- Versatile, general purpose permanent emulsion acrylic adhesive designed for excellent adhesion to corrugated cardboard and superior adhesion to plastics
- Excellent initial tack without sacrificing high speed converting
- Bleached super calendered kraft stock featuring high internal strength, toughness, and tear resistance
- Used primarily for roll-to-roll label applications
- Not recommended for flexo printing
- For use with all information printing technologies, including laser

Face

Caliper 0.0041 +/- 10% inches

Adhesive

Thickness 0.0007 +/- 10% inches

Peel Adhesion Glass: 1.9 lbs

Temperature Ranges

(24" x 36" 500 sheets)

Minimum Application +38° F (-3°C)

Service Ranges -65° F to +200° F (-54°C to +93°C)

Liner

Caliper 0.0024 +/- 10% inches
Basis Weight 40.5# per ream +/- 10%

Suggested applications

It couples good ink jet print quality with fast ink drying time and is ideal for applications printing variable information in conjunction with full color graphics.

Important:

Meets the requirements of FDA 21 CFR 175.105 for indirect food contact. Compliance to this regulation permits the use of this adhesive in applications for which the adhesive either (1) is separated from the food by a functional barrier, which will prevent the migration of any of the adhesive components to the food, or (2) has incidental contact with food limited to the trace amount at the seams or the edges of the label.

pressiza

Shelf Life

Unless specified otherwise in this document, one year when stored at 72°F at 50% RH

This information is confidential, and restricted for the internal use of RSI México customers for informative purposes, and can not be reproduced or communicated to third parties without our written authorization.

TIJUANA: (664) 215.0679 **PUEBLA:** (222) 225.6594

HERMOSILLO: (662) 369.7306 comunicacion@rsimexico.com

